

32" Self-service Kiosk - Floorstand

The self service kiosk touch screen is an innovative solution that has transformed the food retail industry, providing customers with a convenient self ordering system, QR code scanner, and 24/7 availability. We understand that this technology can greatly benefit your business.



Highlights



QR Code Scanner & Thermal

features an LED light to improve reading ability and can be used to scan barcodes or QR codes in conjunction with special offers or to place orders.



Easy Maintenance & Cleaning

optional Cloud Update
Tool-free maintenance is possible via the lockable front access door, allowing store staff to swap out and replace components without removing from the wall. Touch screen & barcode scanner are recessed into enclosure to wipe clean surface.



24/7 Commercial Use

As many quick service restaurants and supermarkets are open 24/7 any kiosk solution needs to be up to the task of being in continuous use.



Anti-theft Mounting Options

OS
The kiosk can be securely mounted directly to the wall from inside the lockable door providing an anti-theft flush fit. There is also an optional floor stand available on request when wall mounting is not possible



Durable Protective Glass

The glass front is thermally toughened but also has a special anti-scratch 6H hardness coating. There is also a special coating on the panel which reduces annoying reflections created by external light sources.



Integrated Receipt Printer

Integrated receipt printer saves space, speeds up service, and boosts sales by combining dynamic promotions with seamless transaction printing in one sleek device.

Specifications

General

| | |
|------------------------|----------------|
| Model | YJC-320-K |
| Screen Size | 32" |
| Screen Active Area(mm) | 698×393 |
| Resolution | FHD(1920×1080) |
| Aspect Ratio | 16:9 |
| Brightness(nits) | 300 nits |
| Contrast Ratio | 1200:1 |
| Viewing Angle(H/V) | 178°/178° |
| Backlight Life Cycle | 50,000 Hrs |
| Operation Hours | 24/7 |
| Response Time | 6ms |
| Screen Orientation | Portrait |

System

| | |
|----------|--|
| OS | Android 11 |
| CPU | RK3568, Quad-core 2.0GHz |
| GPU | The Mali-G52 GPU supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.0, and Vulkan 1.1. |
| DDR | DDR 2GB |
| ROM | 32GB EMMC |
| Language | English/Multilingual |

Connectivity

| | |
|-------|--------------------------|
| Input | USB x2, Ethernet RJ45 x1 |
|-------|--------------------------|

Network connection

| | |
|------------------|----------|
| Wifi or LAN | Yes |
| 3G/4G connection | Optional |

Speaker

| | |
|--------------------|-----|
| Build in speaker | Yes |
| BT Speaker Support | Yes |

Power

| | |
|-------------------|---------------------|
| Power Supply | AC 100~240V,50/60Hz |
| Power Type | Built-In Power |
| Power Consumption | 39W(Max.) |

Physical

| | |
|---------------------------|---|
| IP rating | IP5X |
| Glass | Yes |
| Shell | Cold-rolled steel sheet |
| Standard Color | Black + White |
| Dimensions | 1898.6(H)×520(W)×190(D) mm |
| Net Weight | 27 kg |
| Packing Dimensions(W×H×D) | 1250 x 600 x 260 mm 890 x 230 x 400 mm |
| Installation Method | Floorstand |

Operations

| | |
|-----------------------|---------------|
| Working environment | Indoor |
| Operation Temperature | 0°C to 45°C |
| Operation Humidity | 10% to 80% |
| Storage Temperature | -10°C to 50°C |
| Storage Humidity | 10% to 80% |

What's in the box

| | |
|-------------|----------------------------------|
| Accessories | Power cable x 1 |
| | Screw package x 1 |
| | POS bracket x 1 |
| | Antenna |
| | User Manual (Electronic Version) |

Dimensions

